

3. コネクター表 56 PIN CONNECTOR

Conforming to JAMMA standard (3.96mm pitch)

Gun Force

SOLDER SIDE			PARTS SIDE
GND	A	1	GND
GND	B	2	GND
+5V	C	3	+5V
+5V	D	4	+5V
	E	5	
+12V	F	6	+12V
MISINSERTION PREVENTING KEY COIN COUNTER B	H	7	MISINSERTION PREVENTING KEY COIN COUNTER A
	J	8	
	K	9	
SPEAKER (-)	L	10	SPEAKER (+)
	M	11	
GREEN	N	12	RED
SYNC	P	13	BLUE
SERVICE SW	R	14	GND
	S	15	
COIN. B.	T	16	COIN. A.
2P START	U	17	1P START
2P UP	V	18	1P UP
2P DOWN	W	19	1P DOWN
2P LEFT	X	20	1P LEFT
2P RIGHT	Y	21	1P RIGHT
2P ATTACK	Z	22	1P ATTACK
2P JUMP, GET ON/OFF VEHICLES	a	23	1P JUMP, GET ON/OFF VEHICLES
	b	24	
	c	25	
	d	26	
GND	e	27	GND
GND	f	28	GND

N.B.

Use two 8-way joysticks, each with two push-button switches, and a horizontally placed CRT monitor.

