PITFALL (834-5627)

COIN/CREDIT OPTIONS SWITCH SETTING

-	-	CHAR	TCH	
- 131		SW	псн	- E A

OFF ON OFF ON OFF ON OFF ON	OFF OFF ON ON OFF ON OFF ON OFF	OFF OFF OFF ON ON ON OFF OFF	OFF OFF OFF OFF OFF OFF ON ON	OFF ON OFF ON OFF ON OFF ON	OFF OFF ON OFF ON ON OFF ON ON OFF OFF	OFF OFF OFF ON ON ON OFF OFF	OFF OFF OFF OFF OFF ON ON
OFF	OFF	OFF	ON	ON	OFF	OFF	ON
		OFF	ON	OFF	ON	OFF	.on
ON		-					1
	ON	OFF	ON	ON	ON	OFF	ON
OFF	OFF	ON	ON	OFF	OFF	ON	ON
ON	OFF	ON	ON	ON	OFF	ON	ON
OFF	ON	ON	ON	OFF	ON	ON	ON
ON	ON	ON	ON	ON	ON	ON	ON
	OFF ON	OFF ON	OFF ON ON	OFF ON ON ON	OFF ON ON ON OFF	OFF ON ON ON OFF ON ON ON ON ON	OFF ON ON ON OFF ON ON ON ON ON ON

DIP SW B DIP SW A BARE BD No. 171-5034 171-5054


171-5054-01


COMPONENT SIDE SOLDER SIDE GND GND BLUE CMP SYNC RED - GREEN - SPEAKER SPEAKER SERVICE SW. NOT USED TEST SW. NOT USED COIN SW 2 - 2P START COIN SW 1 - 1P START 1P LEFT 2P LEFT -IP RIGHT 2P RIGHT 1P UP 2P UP 1P DOWN - 2P DOWN NOT USED NOT USED 1P JUMP 2P JUMP NOT USED NOT USED NOT USED NOT USED +12V NOT USED COIN METER 1-COIN METER 2 + SV } + 5V GND } GND

44PIN P=3.96mm

OPTION SWITCH SETTING

OPTION	4	1	2	3	4	5	6	1 ,	8	
TABLE UPRIGHT		OFF ON	Ì				-	Ĺ		
ADVERTISE SOUND	OFF ON		OFF ON							
NUMBER OF PLAYERS	3 MEN 4 MEN 5 MEN FREE			OFF ON OFF ON	OFF OFF ON ON				ON	
SCORE OF ADDITIONAL PLAYERS	20008-5000 20008-7000							OFF ON		
NOT CONTINU	E						OFF ON			
GAME DIFFICULTY	NORMAL HARD							OFF		





SUPPLY VOLTA	GES & CURRENT			
VOLTAGE	CURRENT			
DC5V	4.1A			
DC12V	0.25 A			